

Material And Finish

Shell: Steel
Nickel plated

Insulator: PBT with glass-fiber reinforcement
UL 94V-0
color-black

Contact Material:
Plug - Brass

Contact Plating Options:

Standard:
Gold flash over Nickel on contact area. Tin over Nickel on soldertails

-15 Option:
15u" Gold over Nickel on contact area. Tin over Nickel on soldertails

-30 Option:
30u" Gold over Nickel on contact area. Tin over Nickel on soldertails

Electrical Specifications

Rated Current: 2A

Rated Voltage: 30V RMS

Dielectric Withstanding Voltage:
1000 V (rms) AC for 1 minute

Insulation Resistance:
more than 1000 Megohm at 500 V DC

Contact Resistance:
13 milliohm Max

Temperature Rating:
-55°C to +105°C

Part Number	Contact Area Plating Finish
K88X-AD-15P-BR	Gold Flash (standard)
K88X-AD-15P-BR15	15u" Gold (15 option)
K88X-AD-15P-BR30	30u" Gold (30 option)

Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

RoHS COMPLIANT




REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	10/27/06	New Drawing	R. Aguirre	H. MA	R. Aguirre	10/27/06
A2	1/24/08	ECO# 07-052	WILL H.	H. MA		
A3	12/31/17	ECO #17-035	G. Serrato	C. Furumasu		

K88X-AD-15P-BR

Vertical PCB Mount D-Sub Connector

15 pos. Male , Threaded Bushings



UNITS
mm