



MODULAR JACKS WITH MAGNETICS: G15LX Series

MAGJACK, 10G MAGNETICS, TAB DOWN, FULL SHIELD NO TABS

Product Features

- 10G magnetics
- Fully shielded
- Right-angle, through-hole
- With BST circuit
- Tab-down
- 1 green and 1 yellow LED
- 30u" Gold plated contacts
- 10-pin signal pin layout
- No EMI tabs

Performance Specifications

Materials and Finish

Housing Material:

High Temperature Thermoplastic,
UL 94V-0 Rated, Color: Black

Shield

Brass, Nickel Plated

Contact Material

Phosphor Bronze

Contact Plating

Nickel Underplating,
with 30u" Gold Plating on Contact Area,

Electrical Characteristics

Dielectric Withstanding Voltage

2250V DC for 60 Seconds
Primary to Secondary

Mechanical Characteristics

Mating Force: 23N Max.

Durability Rating

750 Mating Cycles Min.


Operating Temperature

-40°C to +85°C

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number

Part Number Builder



Series

G15LX-110 - Right angle, tab down, guide pegs

Shield Options

S - Fully Shielded, No Tabs

Options

10G - 10G Magnetics

LED Color

G/Y - Green/Yellow

Plating

30 - 30u Gold

Contact Kycon for Schematics Options

G15LX Series

Dimensions in mm

