



Recommended PCB Layout
(Top View)

Materials and Finish

Housing Material-
PBT Thermoplastic
UL 94V-0 Rated
Color: Black

Design meets UL 1863 Sec. 8
Electrical Probe and Sec. 20
Child Finger test requirements

Contact Material-
Phosphor Bronze

Contact Plating Options-
Standard: 0.0001" Nickel
Plating, Selective Plating
Gold Flash on Contact
Area, Gold on Entire Contact

50: 0.0001" Nickel Plating,
Selective Plating 0.000050"
Gold on Contact Area to
Comply with FCC Requirements
Under No. 47 C.F.R. Part 68,
Subpart F, Gold on Entire Contact

Electrical Characteristics

Current Rating-
1.5 Amps

Voltage Rating-
125V DC

Insulation Resistance-
500 Megohms min.

Dielectric Withstanding Voltage-
1000V rms, 60Hz

Contact Resistance-
20 milliohms max.

Operating Temperature-
-40°C to +80°C

Durability Rating-
500 mating cycles min.

Part Number	Contact Area Plating Finish
GMX-N-88	Gold Flash (standard)
GMX-N-88-50	50u" Gold (50 option)

Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise



REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	05/09/05	New Drawing	R. Aguirre	H. MA	R. Aguirre	5/03/05
A2	05/13/10	ECO #10-025	S. Vien	H. MA		
A3	12/12/13	ECO #13-091	D. Gih	H. MA		
A4	03/09/17	ECO #17-005	G. Serrato	W. Cook		
A5	06/12/17	ECO #17-014	H. MA	C. Furumasa		

GMX-N-88-xx

Right Angle Modular Jack

8P8C, RoHS Compliant

